



NOTES:

- 1) .003 MAX ALLOWABLE BOW
- 2) PIN TIPS ARE PARABOLA REVOLVED
- 3) TUMBLE TO MINIMIZE BURRS

| | | | | |
|--|------------------------------------|------|---------------------------------|---|
| UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± THREE PLACE DECIMAL ± | ORIGINAL BY | NAME | DATE | www.BeadElectronics.com TITLE: W025-059A |
| | UPDATED BY | K.L. | 1/9/90 | |
| | ENG APPR. | T.P. | 7/7/10 | |
| | MFG APPR. | | | |
| INTERPRET GEOMETRIC TOLERANCING PER: | Q.A. | | | SIZE DWG. NO. REV A A |
| MATERIAL CDA 510 | COMMENTS: | | SCALE: 1:1 WEIGHT: SHEET 1 OF 1 | |
| FINISH | REVS. A-PLATING CHANGE PER Q.C. | | | |
| DO NOT SCALE DRAWING | | | | |



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BEAD INDUSTRIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BEAD INDUSTRIES IS PROHIBITED.