



- NOTES:
- 1) TANDEM PIN ®
  - 2) WIND LONG END FIRST ONTO REEL, END USER TO UNWIND SHORT END FIRST
  - 3) WIND 50,000 PER REEL
  - 4) MANUFACTURED TO ENGLISH UNITS
  - 5) BRIGHT TIN-PLATE .000190" MIN OVER NICKEL .000080" MIN

UNLESS OTHERWISE SPECIFIED:	NAME	DATE
DIMENSIONS ARE IN INCHES	J.B.	7/25/06
TOLERANCES:	UPDATED BY	8/3/10
FRACTIONAL ±	ENG APPR.	
ANGULAR: MACH ± BEND ±	MFG APPR.	
TWO PLACE DECIMAL ±	Q.A.	
THREE PLACE DECIMAL ±	COMMENTS:	
INTERPRET GEOMETRIC TOLERANCING PER:		
MATERIAL		
CDA 260 BRASS		
FINISH		
SEE NOTE - 5 -		
DO NOT SCALE DRAWING		

www.BeadElectronics.com		
TITLE:		
W040-432ACA		
SIZE	DWG. NO.	REV
A		
SCALE: 1:1	WEIGHT:	SHEET 1 OF 1



**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BEAD INDUSTRIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BEAD INDUSTRIES IS PROHIBITED.